



No	VA503
Revision	17
Aircraft	GippsAero GA8 & GA8-TC 320
Date	3 March 2011

TYPE CERTIFICATE DATA SHEET

This data sheet, which is part of Type Certificate No. VA503, lists the conditions and operational limitations under which the subject aircraft meets the airworthiness requirements of the Civil Aviation Safety Authority.

Certificate Holder GA8 Airvan Pty Ltd
ACN 119 523 830
C/- GippsAero Pty Ltd
Latrobe Regional Airport, Airfield Road
Traralgon, Victoria, Australia 3844

I Model GA8. Approved in Normal Category 10 October 2000

Engine Textron Lycoming IO-540-K1A5

Engine Limits Take Off 2500 rpm and full throttle (275 hp), or
2700 rpm and full throttle (300 hp) – max 2 minutes
(See Note 5).
Maximum Continuous 2500 rpm and full throttle (275 hp)

Propeller Hartzell HC-C2YR-1BF/F8475R two blade, constant speed
Diameter not over 2134 mm
not under 1981 mm
Minimum Blade Angle 12.4 degrees

or

Hartzell HC-C3YR-1RF/F8068 three blade, constant speed (See Note 8)
Diameter not over 2083 mm
not under 1981 mm
Minimum Blade Angle 12.8 degrees

Serial Numbers Eligible GA8-00-004 and subsequent. See Note 9.

II Model GA8-TC 320 Approved in Normal Category 9 February 2009

Engine	Textron Lycoming TIO-540-AH1A	
Engine Limits	Normal Take Off	2500 rpm and 38 in Hg MAP (300 HP)
	Alternate Take Off	2500 rpm and 40 in Hg MAP below 5000' Pressure Altitude (See Note 7).
	Maximum Continuous	2500 rpm at 38 inHg (300 hp)
Propeller	Hartzell HC-C3YR-1RF/F8068 three blade, constant speed	
	Diameter	not over 2083 mm not under 1981 mm
	Minimum Blade Angle	16.1 degrees
Serial Numbers Eligible	GA8-TC-320-09-120, GA8-TC-320-08-130 and subsequent.	

Data Pertinent to All Models

Fuel	100LL or 100/130 aviation gasoline	
Airspeed Limits	For aircraft incorporating SB-GA8-2011-65 or SB-GA8-2011-66:	
	Never exceed V_{ne}	190 KIAS (knots IAS)
	Max structural cruise V_{no}	147 KIAS
	Manoeuvring V_a	121 KIAS
	Max flaps extended V_{fe}	100 KIAS
	For all other aircraft:	
	Never exceed V_{ne}	185 KIAS
	Max structural cruise V_{no}	143 KIAS
	Manoeuvring V_a	121 KIAS
	Max flaps extended V_{fe}	97 KIAS
Centre of Gravity Limits	For aircraft incorporating SB-GA8-2011-65 or SB-GA8-2011-66:	
	Forward Limit	+1219 mm aft of datum at 1089 kg or less
		+1448 mm aft of datum at 1905 kg
	Variation is linear between 1089 kg and 1905 kg.	
	Aft Limit	+1626 mm aft of datum at all weights
	For all other aircraft:	
	Forward Limit	+1219 mm aft of datum at 1089 kg or less
		+1422 mm aft of datum at 1814 kg
	Variation is linear between 1089 kg and 1814 kg.	
	Aft Limit	+1626 mm aft of datum at all weights
Datum	Fuselage firewall frame jacking points at fuselage station 0 (Stated arms are +ve aft; and -ve forward)	
Levelling Means	Longitudinal Marks (blind rivets) on the port fuselage wall Lateral Level across cockpit seat rails	

Maximum Weights	For aircraft incorporating SB-GA8-2011-65 or SB-GA8-2011-66:		
	Take-off	1905 kg	
	Landing	1814 kg	
	For all other aircraft:		
	Take-off	1814 kg	
	Landing	1814 kg	
No. of Seats	Eight	Row 1 (Pilot row)	arm + 965 mm
		Row 2	+1772 mm
		Row 3	+2523 mm
		Row 4	+3247 mm
Maximum Baggage Aft Luggage	Baggage Shelf	113kg	at +3763 mm
	Bin	22kg	at +4623 mm
Fuel Capacity	Main wing tanks	two (one tank in each wing)	
	Total each tank	170 litres	at +1715 mm
	Useable each tank	166 litres	at +1715 mm
	Unusable each tank	4 litres	at +1829 mm
	Sump tank	9 litres	at +705 mm
	Sump tank capacity is designated unusable fuel.		
Oil Capacity	Total	11.4 litres	at -540 mm
	Unusable	2.6 litres	at -540 mm
Crosswind Component	Maximum demonstrated for take-off and landing 15 knots		
Control Surface Deflections	Horizontal Stabiliser leading edge	Up	2.0° ± 0.5°
		Down	5.0° ± 0.5°
	- measured between the mid-section line of the stabiliser and the horizontal reference		
	Elevator trailing edge	Up	15.0° ± 0.5°
		Down	19.0° ± 0.5°
	- measured between the mid-section line of the elevator and the mid-section line of the horizontal stabiliser, with the stabiliser in the full leading edge down position		
	Aileron trailing edge	Up	17.0° ± 0.5°
		Down	16.0° ± 0.5°
	- measured between the under-surface of the aileron and the rear under-surface of the wing main plane		
	Rudder trailing edge	L & R	21.0° ± 0.5°

Wing flaps	Retracted	$0^{\circ} \pm 1^{\circ}$
	Take-off	$14.0^{\circ} \pm 1^{\circ}$
	Landing	$38.0^{\circ} \pm 1^{\circ}$

All measurements refer to hinge line rotation.

Type Design Data

For Model GA8 aircraft, serial numbers GA8-00-004 to GA8-03-025:

- (i) Engineering Release GA8-970001, Issue 5 or later approved revision,
- (ii) Master Drawing GA8-010001, Issue 2 or later approved revision, GA8 General Assembly,
- (iii) Pilot's Operating Handbook and Approved Flight Manual, document C01-01-01, dated 10 September 2001 or later approved revision; or for aircraft incorporating SB-GA8-2005-10, document C01-01-06, dated 8 August 2005 or later approved revision (see Note 5), and
- (iv) Service Manual document C01-00-01, Chapter 4 Airworthiness Limitations, dated 26 November 2001 or later approved revision.

For Model GA8 aircraft, serial numbers GA8-03-026 and subsequent,

- (i) Engineering Release GA8-970002, Issue 1 or later approved revision,
- (ii) Master Drawing GA8-010001, Issue 3 or later approved revision, GA8 General Assembly,
- (iii) Pilot's Operating Handbook and Approved Flight Manual, document C01-01-03, dated 14 March 2003 or later revision or, for aircraft incorporating SB-GA8-2005-10, document C01-01-07, dated 8 August 2005 or later approved revision, (see Note 5), and
- (iv) Service Manual document C01-00-03, Chapter 4 Airworthiness Limitations, dated 14 March 2003 or later approved revision.

For Model GA8-TC 320 aircraft:

- (i) Engineering Release GA8-970004, Issue 1 or later approved revision - GA8-TC 320 Master Data Package.
- (ii) Pilot's Operating Handbook and Approved Flight Manual, document C01-01-08, dated 23 January 2009 or later approved revision and
- (iii) Service Manual document C01-00-05, Chapter 4 Airworthiness Limitations, dated 19 December 2008 or later approved revision.

Additional Type Design Data for IFR approved aircraft

- (i) Engineering Release GA8-970003, Issue 1 or later approved revision
- (ii) Pilot's Operating Handbook and Approved Flight Manual as above. (See Notes 3 and 5)

Certification Basis	<ol style="list-style-type: none">1. Part 21 of the Civil Aviation Safety Regulations 1998, and2. For aircraft serial numbers GA8-00-004 to GA8-03-025, Federal Aviation Regulation, Part 23 at Amendment 48, except paragraph 23.629 which is at Amendment 45.3. For aircraft serial numbers GA8-03-026 and subsequent, Federal Aviation Regulations, Part 23 at Amendment 54. <p>See Note 5 for noise certification.</p>
Production Basis	Production Certificate No. 053049, dated 15 August 2003 or Production Certificate No. 793691, dated 6 May 2010
Equipment	<ol style="list-style-type: none">1. The CASA approved aircraft flight manual details required equipment for kinds of operations.2. Other equipment may be required, to meet applicable operational regulations.
Placards	The placards detailed in the applicable CASA approved aircraft Pilot's Operating Handbook and Approved Flight Manual are required to be fitted.
Notes	<ol style="list-style-type: none">1. Weight and Balance. A current weight and balance report including a list of equipment included in the certificated empty weight, an approved load data sheet and an approved loading system, must be provided for each aircraft at the time of issue of a Certificate of Airworthiness.2. Aircraft serial numbers GA8-00-004 to GA8-03-025 may have their certification standard upgraded to FAR 23 Amdt 54 by incorporating Service Bulletin SB-GA8-2003-04 (see Note 6). Aircraft so upgraded are required to have Pilot's Operating Handbook and Approved Flight Manual, document C01-01-03, dated 14 March 2003 (or later) or, for aircraft incorporating SB-GA8-2005-10, document C01-01-07, dated 8 August 2005 (or later), (see Notes 5 and 6).3. Aircraft which are not manufactured with IFR capability may be modified to be IFR capable by complying with Service Bulletin SB-GA8-2003-08 (see Note 6).4. Cargo Pod Installation options GA8-255004-11, GA8-255004-15, GA8-255004-17 or GA8-255004-19 is approved when incorporated in accordance with Service Bulletin SB-GA8-2004-14 (see Note 6).5. Noise certification has been carried out by Airservices Australia. The certification basis for noise is as follows:<ol style="list-style-type: none">(i) Aircraft with engine take-off limits of 2500 rpm meet ICAO Annex 16 Volume 1 Chapter 10, Third Edition, Amendment 6. These aircraft require aircraft flight manual C01-01-01 or C01-01-03 (see Type Design Data above), and(ii) Aircraft with engine take-off limits of 2700 rpm meet Federal Aviation Regulations Part 36, Appendix G, Amendment 24. These aircraft require

aircraft flight manual C01-01-06 or C01-01-07 (see Type Design Data above).

- (iii) Noise certification is pending for aircraft incorporating SB-GA8-2011-65 or SB-GA8-2011-66.

Service Bulletins SB-GA8-2005-10 and SB-GA8-2005-16 (see Note 6) provide approved data to convert from one noise certification configuration to the other.

6. Unless otherwise stated, later CASA approved documentation revisions are accepted as meeting type data requirements.
7. The TIO-540-AHIA has an alternate take-off rating of 40.0 in Hg at 2500 rpm limited to 5000 feet pressure altitude.
8. The optional Hartzell HC-C3YR-1RF/F8068 three blade propeller is approved when installed by Gippsland Aeronautics in accordance with Engineering Release GA8-9661149 (Option 149), or when incorporated on a specific aircraft serial number in accordance with Gippsland Aeronautics Service Bulletin GA8-SB-2009-62.
9. When GA8-00-004 and subsequent GA8 aircraft have been modified with the turbocharged engine option, the engine, engine limits, and propeller limits shall be as given for the GA8-TC 320 model.

Revision History

Revision 7 was issued 14 March 2003 to correct mass arms, and to include the later design standard for serial number 026 and subsequent.

Revision 8 was issued 15 September 2003 to include IFR approval and reference to the production certificate.

Revision 9 was issued 25 October 2004 to include the Cargo Pod approval.

Revision 10 was issued to add an alternative noise certification that allows take-off at 2700 rpm and full throttle.

Revision 11 was issued due to a change of Type Certificate holder, from Gippsland Aeronautics Pty Ltd, to GA8 Airvan Pty Ltd.

Revision 12 was issued to incorporate new model GA8-TC 320, and minor editorial and formatting changes.

Revision 13 was issued to correct a minor typographical error on page 4, Additional Type Design Data for Model GA8-TC 320: Paragraph (iii) (date of issue of Service Manual C01-00-05 was changed from 19 December 2009 to 19 December 2008).

Revision 14 was issued to incorporate the optional Hartzell HC-C3YR-1RF/F8068 three blade propeller.

Revision 15 was issued to update Type Certificate Holder details and to incorporate corrections to the certification basis and GA8-TC 320 serial number eligibility.

Revision 16 was issued to update Type Certificate Holder details, add new Production Certificate number, incorporate corrections and clarifications to propeller details, certification basis, serial number eligibility, reference to 'latest issue' on several documents, and several minor editorial changes.

Revision 17 was issued to incorporate changes to the airspeed, centre of gravity, and weight limits when incorporating SB-GA8-2011-65 or SB-GA8-2011-66. Minor formatting changes.

- END -